



Magnetizing Powers

The table of model					
Model	DXD-1520-30	DXD-2520-30	DXD-2530-30	DXD-4030-30	DXD-4060-30
Input Power	AC220V 50~60Hz 30A	AC220V 50~60Hz 40A		AC380V 50~60Hz 60A	
Max Output Current	30,000	30,000		30,000	
Charge Voltage	DC50~1500V	DC50~2500V		DC200~4000V	
Repeat Precision Of Charge Voltage	±1V+1digit	±1V+1digit		±1V+1digit	
Charge Time	5 (sec)	6 (sec)	10 (sec)	12 (sec)	24 (sec)
The Capacity of Condenser	2,000uF	2,000uF	3,000uF	3,000uF	6,000uF
The Capacity Changing	1,000/2,000	1,000/2,000	1,000/2,000/3,000	1,000/2,000/3,000	1,000/2,000/6,000
Main Switch	SCR	SCR		SCR	
Discharge Current Meter (Compare Function)	Have	Have		Have	
Interior Discharge Circuit	Have	Have		Have	
Enclosure Dimensions	600W×900D×1350H	700W×900D×1450H	700W×1180D×1450H	1000W×1000D×1350H	1660W×1000D×2000H
Weight	250Kg	410Kg	510Kg	1200Kg	1800Kg

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>